

ARGOX
Empower the Barcode

ArgoScan
2D Barcode Imager
AS-9500



AS-9500

ARGOX

ArgoScan 2D Barcode Imager AS-9500

Features

- Aiming line for easy-of-use in scanning barcode
- Plug and play connectivity - All popular interfaces are on board including RS-232, USB HID and USB COM port
- Readable under sun light to 100,000 Lux
- Durable - without any moving parts to wear out
- Support scanning 2-Dimensional symbols such as MaxiCode, DataMatrix, QR Code and Aztec, as well as the full range of barcode symbologies.
- Reliability
 - (1) Trigger: 1,000,000 times
 - (2) Cable: 320,000 times (90°)



Applications

Hospitals and Pharmacies
Libraries
Administration
Inventory
E-Government
Customs
Animal husbandry
Automotive industry
Semiconductor
Telecommunication

ARGOX
Empower the Barcode



Product Values




AS-9500

Argox has launched its first 2D scanner, the AS-9500. The new handheld scanner is small, lightweight and easy-to-use, and not only does it read all popular 1D and 2D barcodes, it also reads postal codes and OCR. The AS-9500 works in all environments including bright sunlight up to 100,000 Lux.

The AS-9500 is durable and designed for everyday use, meeting IP42 dustproof and waterproof standards as well as drop tests from 1.5 meters. It connects to other devices via RS-232, USB HID and USB COM port interfaces. The AS-9500 is ideal for use in applications requiring information-rich 2D barcodes, such as hospitals, pharmacies, libraries, government tax bureaus, customs, industry, automotive, and more.



AS-9500

Specifications	AS- 9500					
Focal Point	4.5 inches(11.4cm) from lens plate					
Scan Angle	Pitch: $\pm 40^{\circ}$		Yaw: $\pm 40^{\circ}$			
Resolution	1D:5 mil (0.127mm) min			2D: 8 mil (0.21 mm) min		
Reading indication	LED and adjustable beep sound					
Scanning system	752 X 480 CMOS sensor					
Motion Tolerance	4 inches per second					
Rotational Sensitivity	360 $^{\circ}$					
Illumination LEDs	626nm \pm 30nm					
Aiming	LEDs: 526nm \pm 30nm					
Scan Rate	Up to 60 fps					
PCS	\geq 30%					
Weight	146g					
Interface	RS-232, USB HID, USB Virtual COM					
Depth of Field	PCS = 90%, 1D			PCS = 90%, 2D		
		Near Field	Far Field		Near Field	Far Field
	5 mil (Code39, 1:2.5)	Readable		8 mil (QR)	2.91"	4.44"
	8 mil (Code39, 1:2.5)	2.28"	5.03"	10 mil (QR)	2.44"	5.39"
	10 mil (Code39, 1:2.5)	1.46"	6.89"	13 mil (QR)	1.52"	6.34"
	13 mil (Code39, 1:2.5)	1.53"	8.30"	20 mil (QR)	---	8.79"
	20 mil (Code39, 1:2.5)	---	10.23"	10 mil (PDF417)	2.01"	6.29"
	13 mil (UPC/EAN)	1.38"	8.97"	13 mil (PDF417)	1.99"	7.16"
Symbologies	1D	Code 11, Code 39, Code 32, Code 128, Codabar, Interleaved 2 of 5, Industrial 2 of 5, IATA 2 of 5, Matrix 2 of 5, EAN/JAN-13,EAN/JAN-8, UPC-A, UPC-E, UPC-A/EAN-13 with Extended Coupon Code, Code 93, MSI, Plessey Code, Telepen, PosiCode A and B, GS1 DataBar, Codablock F, TLC 39				
	2D	PDF417, MicroPDF417, MaxiCode, Data Matrix, QR Code, Aztec, Code 49, EAN-UCC Composite Codes, , Code 16K, Chinese Sensible (Han Xin) Code				
	Postal	Postnet (US), Planet Code, Australian Post, British Post, China Post, Canadian Post, Japanese Post, KIX(Netherlands) Post, Korea Post,4-CB, ID-tag				
	OCR	OCR-A, OCR-B, U.S.Currency				
Programming Method	<ul style="list-style-type: none"> ■ Command through RS232 ■ Command through USB virtual com port ■ Scanner read the programming barcode 					
Power supply & Consumption	Operating range: 3.5 VDC to 5.5 VDC RS-232 Scanning : Max 300 mA@5V Idle :Max 55mA@5V USB- HID Scanning : Max 300 mA@5V Idle :Max 50mA@5V					
Agent List	  					
Environment	Operating Temperature: 0 $^{\circ}$ C to +50 $^{\circ}$ C (0 $^{\circ}$ to 122 $^{\circ}$ F) Storage Temperature: -20 $^{\circ}$ C to +60 $^{\circ}$ C (-4 $^{\circ}$ to 140 $^{\circ}$ F) Operating RH: Up to 95% RH, non-condensing at 50 $^{\circ}$ C Ambient LUX: Total darkness to 100,000 lux (full sunlight) Dust& Splash resistance: IP42 Floor Drop: 24 drops from 150 cm to concrete					