

The Versatile P.O.S. 17" TFT LCD Color Monitor



Model		PA-17
LCD Display		17" TFT active matrix panel
Pixel pitch		0.264 mm
Max. Resolution		1280 X 1024 @ 75Hz (max.)
Contrast Ratio		500:1
Brightness		300 cd/m ² (typical)
Response Time (Tr+Tf)		8 ms (typical)
Viewing Angle (CR>10)	L/R	70° / 70°
	U/D	70° / 60°
Lamp Life Time		50,000 hrs
Compatible Digital/Analog	VGA	640 X 350 (70Hz), 720 X 400 (70Hz), 640 X 480 (70Hz),
	VESA	640 X 480 (72/75Hz)
		800 X 600 (60/72/75Hz)
		1024 X 768 (60/75Hz)
		1280 X 1024 (60/75Hz)
Input Signal	RGB Analog	75 ohms, 0.7/1.0 Vp-p
		FH: 30-82KHz FV: 50-75Hz
		H/V Separated (TTL)
External Connector		15-Pin D-Sub X 1 2.0 DC Jack X 1
Key Control		Power, Up, Down, Menu/ Enter
OSD Functions: PC		Brightness, Contrast, Auto Adjust, Clock, Phase, Color Temperature (9300K, 6500K, User), Volume, Language, OSD Control
Power Input		AC Input 100-240V, 50-60 Hz (Universal)
Power Consumption		36W (MAX.)
Power Management		VESA DPMS Standard
Operating Conditions	Temperature	0°C-40°C (32°F-104°F)
	Humidity	10%-90% (non-condensing)
Dimensions		378mm (W) x 367mm (H) x 188mm (D)
Weight		N.W.: 4.9 Kg
Certification		UL/CUL/FCC-B/CD/CE/TUV/GS
Warranty		One-year limited warranty on parts, labor and backlight

PA-17



PA-17



Unit:mm

Specification is subject to change without notice. 2008. 11



TAIWAN VIDEO SYSTEM CO., LTD.

3f-1., No.196, Xinhua 3rd Rd., Neihu District, Taipei City, Taiwan, R.O.C. 114
TEL: 02-8791-2600 FAX: 02-8791-9016
http://www.tvs.com.tw E-mail: info@tvs.com.tw

TVS GROUP

USA TVSA e-mail: info@eversun.com
Germany TVSG e-mail: info@tvsg.de
China TVSC e-mail: info@tvsc.com.cn

