

WavePOS 6860



Ready in Windows System



Flat Touch Screen



LCM Customer Display



Hard Disk Quick Maintenance



2nd LCD Display

MODEL	WavePOS 6860	
CPU	Intel® Sky Lake Core™ i3 / i5 / i7 Processor	Intel® Celeron® Elkhart Lake J6412 Processor
Memory	4GB DDR4 SO DIMM Slot up to 16GB	4GB DDR4 SO DIMM Slot up to 16GB
Storage	2.5" SATA SSD, up to 1TB	1 x 2.5" SATA SSD, up to 1TB 1 x M.2 2242 SATA
Power Supply	90W (12V)	60W (24V)
Display	15" TFT-LCD	
Resolution	1024 x 768	
Touch Screen	PCAP Multitouch Screen	
Brightness	300 nits	400 nits
Weight	6.0 kgs	5.8 kgs
Dimensions	360 x 324 x 230 (W x H x D)	
Speaker	2 x 2W	N/A
OS	POSReady 7, Windows 7/8/10	Windows 10 IoT
Certifications	CE /FCC	
Environment	0°C ~ 40°C, 20% ~ 80% RH (Operating) -20°C ~ 60°C, 10% ~ 90% RH (Storage)	
I/O	4 x COM (DB9), 1 x 12V C/D (RJ11), 2 x USB 3.0, 2 x USB 2.0, 1 x Giga LAN (RJ45), 1 x LPT, 1 x VGA, 1 x 12V DC-IN	3 x COM (RJ45), 1 x 12V/24V C/D (RJ11), 3 x USB 3.0, 1 x USB 2.0, 1 x Giga LAN (RJ45), 1 x Video Port, 1 x 24V DC-IN
Peripheral	1D or 2D Scanner, NFC, MSR, IC Card Reader, Wifi b/g/n/ac, LCM, 2nd Display	